

DN 532/533 RIFLESCOPE SERIES

A unique universal day / night riflescopes, features two interchangeable eyepieces for day and night use. Replace daytime eyepiece with a night vision and the scope is ready for action, no re-zeroing or tools are required! DN 532 / 533 is offered with either 7x or 11x magnification. With optional IR illuminator these scopes enable shooting in total darkness.

DN 532 / 533 night vision eyepiece can also be used as a stand alone 1x night vision monocular. With an add-on NVS Lens 3x the monocular turns into a 3x observation device. Built-in windage and elevation adjustment mechanism, matte-black body finish and water resistant design make these scope indispensable when 24/7 operation ability is required.



Night time eyepiece

APPLICATIONS:

- Night surveillance / Hunting
- Police / Law Enforcement
- Patrol / Search and Rescue

FEATURES:

- Interchangeable day / night eyepieces - keep rifle zeroed day and night
- Vision range is 400-1000 m and 100-250 m in total darkness (with optional IR illuminator)
- Night eyepiece also works as a standalone 1x monocular (or 3x with optional lens)
- Unique high-quality day/night optics (100 mm / F1.5 or 166 mm / F2.0)
- Wide field of view
- Wide range of focus adjustment
- Accurate internal windage / elevation adjustment knobs with tactile audible clicks and true 1/4 MoA step
- Water resistant
- Optional powerful IR illuminator (75 or 200 mW)



Optical

	DN 532/533-7x	DN 532/533-11x
Model	DN 532/533-7x	DN 532/533-11x
Objective focus length / F number	100 / F1.5	166 / F2.0
Magnification (day/night)	7.0x / 3.7x	11.2x / 6.0x
Field of view(day/night)	3.7 / 7.4	2.3 / 4.6
Objective lens diameter	66 mm	83 mm
Eye relief	60 mm	60 mm
Dioptre correction	- 4 ...+ 2	- 4 ...+ 2

Mechanical

Battery	1xCR123 Lithium	1xCR123 Lithium
Voltage	3 V	3 V
Battery life minimum	40 h	40 h
Length	340x82x82 mm	440x83x83 mm
Weight (day/night)	990 g / 1.05 kg	1.17 kg / 1.23 kg

Environmental

Operating temperature	-40°C ... +55°C	-40°C ... +55°C
Relative humidity	Up to 98 %	Up to 98 %

Configurations

Model	DN 532	DN 533
Generation	18mm, Gen. 2+	18mm, Gen. 3

