

HOLSAG CANADA

Seating Manufacturer

Specifications: Dakota Chair and Barstool

Description

The Dakota chair and barstool are a contemporary styled item that adds elegance to any setting.

The solid beech hardwood construction and durable wood finish make the Dakota line extremely sturdy as well as attractive.

Dimensions: Chair

Height	34.5"	87.6 cm
Depth	20.5"	52.1 cm
Seat Width	18.5"	47 cm
Seat Depth	17"	43.2 cm
Seat Height	18"	46 cm
Chair Weight	16 lbs	7.25 kg
Carton Weight		
with 1 chair	26lbs	11.82 kg
Carton Size for 1 Chair		
	18.25" x 22.25" x 37.5"	
	46 cm x 56 cm x 95 cm	
Carton Volume for 1 Chair		
	8.8 cubic feet	

Dimensions: Barstool

Height	43.5"	110.5 cm
Depth	20"	51 cm
Seat Width	18.25"	46.4 cm
Seat Depth	16.5"	41.9 cm
Seat Height	30"	76 cm
Stool Weight	18 lbs	8.18 kg
Carton Weight		
with 1 stool	28 lbs	12.73 kg
Carton Size for 1 Barstool		
	18.5" x 20" x 48"	
	46.3 cm x 50.8 cm x 121.8 cm	
Volume		10.3 cubic feet

Note: The barstool is available in custom seat heights ranging from 24" (61 cm) to 30" (76 cm).

Fabric for upholstered seats

COM (Customer's Own Material) fabric required (chair and barstool): .36 yd (.33 m)

Note: This is the estimated amount based on 54" (137 cm) wide material. The actual amount required may vary depending on special pattern matching and the width of the material.

Stock fabric: Black vinyl is available as a stock fabric.

Cushion Foam: High density 1.5" (3.8 cm) thick on seat

Solid wood seats are available.

Wood

Species: 100% Solid European Beech Hardwood

Construction

Joints: Mortise and tenon. Glued with high solids glue and reinforced with 18 gauge nails, corner blocks and low root woodscrews.

Stain Colors

A wide range of standard stain colors is available as well as custom color matching. (A surcharge will apply to custom colors.)

Standard Barstool Kickplates are brass. Chrome kickplates are available upon request at the same price.

9-Step Finishing Process

1. The bare wood of the assembled chair is thoroughly sanded using 120 grit paper.
2. One coat of stain is sprayed onto the entire chair.
3. The stain is handwiped to ensure an even color and maximum penetration into the wood.

4. The chair is inspected and any necessary adjustments made.
5. One coat of catalyzed sealer is sprayed onto all wood parts to completely seal the wood.
6. Once dry, the sealer is sanded using 320 grit paper.
7. A final sanding is done using Scotch Brite pads to remove any sanding marks.
8. A catalyzed lacquer is sprayed on. This lacquer is very durable and will stand up in a commercial environment.
9. A final inspection is performed prior to packaging to ensure a high level of quality control.



Note: Specifications are subject to change without notice.

Holsag Canada

164 Needham Street
Lindsay, Ontario Canada
K9V 5R7
(705) 878-1970
(888) 745-0721 (U.S. & Canada)
Fax: (705) 878-1864

www.holsag.com