

COMMERCIAL Showerheads

GENERAL SPECIFICATION

S-2272-E2



☐ **S-2272-E2**

Water conserving pressure compensating Autoflo® device reduces flow to a maximum of 2.0 gpm/7.6 lpm. Polished chrome plated.

☐ **S-2292**

1-3/4" brass shank. Spray adjusting T-handle. Brass ball swivel joint. Flow control device reduces flow to 2.5 gpm/9.46 lpm maximum, to meet existing ANSI A112.18.1/CSA B125.1 Standard. Polished chrome plated.

S-2280



OPTIONS

SUFFIX	DESCRIPTION
--------	-------------

☐ BP	Blister pack packaging (S-2292 only)
-----------------------------	--------------------------------------

Brass Showerheads

GENERAL SPECIFICATION

Water conserving pressure compensating Autoflo® device reduces flow to a maximum of 2.5 gpm/9.46 lpm, to meet existing ANSI A112.18.1/CSA B125.1 Standard. Vandal-resistant standard. 1/2" NPT inlet.

S-2285



☐ **S-2280**

Anystream wall mounted showerhead. Rigid brass ball. Spray adjusting T-handle 2-1/2" face. 4 Lexan® deposit resisting plungers with 32 spray channels. Drilled for, but less mounting bolts.

S-2288



☐ **S-2288**

Watersaver showerhead. Brass shank. Brass adjustable spray face. Brass ball swivel joint.

☐ **S-2285**

Watersaver showerhead. Rigid brass head. Adjustable spray. Drilled for, but less mounting bolts.

S-2292



☐ **S-2460**

Solid brass wall mounted showerhead. 2" face. 60 spray channels at three different angles to allow a full coverage shower. Drilled for, but less mounting bolts.

OPTIONS

SUFFIX	DESCRIPTION
--------	-------------

☐ AP	Anchor plate assembly with mounting screws (not S-2288)
☐ BJ	Ball joint (S-2280 & S-2285 only)
☐ BPT	1/2" British pipe thread inlet (S-2288 only)
☐ 2	S-2252 Anystream showerhead (S-2280 only)

S-2460



This space for Architect/Engineer approval.

